



SHARPEYES

SHARPEYES INTERACTIVE FLAT DISPLAY

SHARPEYES IFD display is ideal for education, corporate applications. Compared to previous generation displays, this model's LED backlighting allows for reduced power consumption, a thinner depth, a smaller bezel and lighter weight. High definition resolution delivers stunning image quality for a variety of content. It also offers users touch screen capabilities for up to ten simultaneous touches at a cost-conscious price. Its anti-glare glass coating protects the panel and allows for higher brightness transmittance. The touch screen, high-performance panel and abundant advanced technologies promote extended use, making sharpeyes's solution ideal for schools, corporate and retail.

Feel in difference by your finger and eyes, and together successful!



| SPECIFICCATIONS | | |
|--------------------|---------------------|--------------------------------|
| Led Parameters | Model | SH-PNL4055 |
| | Size | 54.6" |
| Packing Parameters | External Size | 1267*743mm |
| | Touch Size | 1212.6*684.61mm |
| | Plywood Carton Size | 1380*170*880mm |
| | Net weight | 35kg |
| | Gross Weight | 40kg |
| Power Parameters | Power | < 200W |
| | Standby Power | < 1 W |
| Display Parameters | Active Display Area | 1212.6*684.61mm |
| | Pixel Pitch | 0.630(h)x0.630(v)mm |
| | Display Colors | 16.7M/1.06B (8-bit/8-bit +FRC) |
| | Number of Pixels | 1920x1080 pixels |
| | Brightness | 400cd/m2 |



For more information email info@sharpeyes.com.vn or visit www.sharpeyes.com.vn

| | | |
|------------------------|----------------------------------|---|
| | Viewing Angle | 178 Degree |
| T V Parameters | TV Standard | NTSC M/N,PAL BG/DK/I/H,SECAM L/L |
| | USB System Upgrading Online | Support USB online upgrading function |
| | Resolution | Max. 1080P format |
| | HDMI | V1.3, 720P/1080P |
| | HDCP | V1.1 |
| | 3D DNR | Support 3D video DNR |
| | Scanning Format | Support 1080i 3D Video crisscross DAS (Dynamic Adaptive Scan) |
| | Sound Output | 2X10W |
| Input and output ports | USB front Multimedia Input ports | 2-line |
| | Touchscreen port | 1-line |
| | HDMI Input port | 3-line |
| | VGA Input port | 2-line |
| | PC Audio port | 1-line |
| | AV Input port | 2-line |
| | S-VIDEO port | 1-line |
| | SPDIF port | 1-line |
| Touchparameters | Touch Technology | Hybr touch distributed by DIR |
| | Touch mode | Single, multipoint, Mouse click |
| | Inductive objects | Finger, pen or any other opaque objects |
| | Inductive size | Diameter≥5mm |
| | Resolution | 32767*32767 |
| | Response time | 1) First dot(click):8ms, continuously(writing):3ms 2) multipoint click:first dot(click):8ms,continuously(writing):8ms 3) Mouse click:first dot(click):8ms,continuously(writing):8ms |
| | Operating life | ≥60,000,000 times to click |
| | Power | USB power supply (4.6-5V, DC) |
| | Power consumption | ≤1w |



| | | |
|---------------------------------|------------------|--|
| | Operation System | Window 7/8/10, Mac, Linux |
| | Calibration | HID devices standard, accord with Win7 multi-touch protocol, no need special software to calibrate, just use Table PC setting to finish the calibration. |
| Standard Accessories without PC | Remote Control | TV Remote control |
| | USB touch cable | 1.5m USB cable for touch monitor, USB2.0 |
| | Pens without ink | 1 pcs |
| | Teaching Pointer | 1 pcs |
| | HDMI cable | 1 pcs |
| | power cable | 1 pcs with 1.5M |
| | Wall brackets | Screws, wall mount kits |

The specification can change without note.



SHARPEYES the “Pro” in IFD

Feel in difference by your finger and eyes, and together successful!



For more information email info@sharpeyes.com.vn or visit www.sharpeyes.com.vn

Printed in by SHARPEYES